Data Sheet

ADSL Barricade™ g SMC7804WBRB

54 Mbps Wireless 4-port Router with built-in Annex B-UR2 ADSL Modem

The ADSL BarricadeTM g, SMC7804WBRB, is an all-in-one solution for connecting and sharing your ADSL Broadband connection in your home or office. This multifunctional Annex B-UR2 ADSL router combines a 2.4GHz 54Mbps 802.11g Wireless Access Point, 4 10/100Mbps RJ45 ports for connection to a PC or Network and an RJ45 WAN port that connects to your ADSL line. The four 10/100Mbps RJ45 ports can be connected to a network hub or switch to expand the number of people sharing your ADSL connection in your home or your office.

The SMC7804WBRB also has a built in DHCP server to make implementing and expanding your network simple and easy. This device supports Full-rate G.dmt, which gives you download speeds of 8Mbps and upload speeds of 640Kbps. Its NAT based Firewall security provides a high level of security for your network. This new device is a complete ADSL solution for PC or MAC users. Graphical user interface software is provided for easy installation, configuration, and management. The LED display panel on the front of the product shows at-a-glance the Ethernet activity, ADSL status and Power. All SMC products are backed by a limited lifetime warranty (5 years) and Free technical support.

Features and Benefits

High Speed Internet Access

- The SMC Wireless ADSL Barricade provides unrivaled asymmetric high-speed data transport over a single copper pair linking Branch Offices, Home Offices & Individual Subscribers to their Network Service Providers, including Internet Service Providers.

Flexibility and Scalability

- The SMC Wireless ADSL barricade is scaleable as the network grows. It brings together the best combination of ADSL technology and the flexibility of Ethernet & Wireless Lan Networks. This flexibility provides maximum performance allowing multiple computers to share local resources, access the Internet simultaneously & keeps you „always connected!"

Easy Setup

- The SMC Wireless ADSL Barricade can be configured and managed locally and remotely via a Web-based configuration tool.
- Investments are protected through the support of popular DSL connection models such as PPP over Ethernet (PPPoE) bridging and routing
- The ADSL Barricade can even support PPP over ATM (PPPoA), bridging and routing.

Security

- The SMC Wireless ADSL Barricade also provides extensive firewall for network protection, VPN pass through (IPSec, PPTP & L2TP) capabilities for reduced cost and remote access communications and DHCP support for Plug-and-Play installations.

Features

- Functions as a Bridge and/or Router
- Ethernet and Wireless Access Point provide greater flexibility for simultaneous sharing of the ADSL and local resources
- Firewall security with WEP, WAP and 802.1x for wireless security
- Remote management and firmware upgrade
- UPnP and Dynamic DNS for Web and Internet appication support

Product	Model No	Description
ADSL Barricade g	SMC7804WBRB	54 Mbps Wireless 4-port Router with built-in ADSL (AnnexB-UR2) Modem

www.smc-europe.com www.smc.com

SMC® Networks

ADSL Barricade™ g
SMC7804WBRB

54 Mbps Wireless 4-port Router with built-in Annex B-UR2 ADSL Modem

Specifications

Physical Characteristics

Ports
- Four 10/100Mbps RJ45 Ports
- One ADSL RJ45
- Two external dipole antennas

ADSL Feature
- Supports DMT line modulation
- Supports Annex A Full-Rate ADSL: up to 8Mbps downstream,
- up to 1Mbps upstream (G.992.1 &T1.413, Issue 2)
- Supports G.Lite ADSL: up to 1.5Mbps downstream, up to 512Kbps upstream
- Dying GASP support

ATM Feature
- RFC1483 Encapsulation (IP, Bridging & encapsulated routing)
- PPP over ATM (LLC &VC multiplexing) (RFC2364)
- Classical IP (RFC1577)
- Traffic shaping (UBR, CBR)
- OAM F4/F5 support
- PPP over Ethernet Client

Management Feature
- Firmware upgrade via WEB Based Management
- WEB Based Management (configuration)
- Power Indicators
- Event &History logging
- Network Ping
- SNMP v.1/2 support

Security Feature
- Password protected configuration access
- User authentication (PAP/CHAP) with PPP
- Firewall NAT NAPT
- VPN pass through (IPSec-ESP Tunnel mode,L2TP, PPTP)

LAN Feature
- IEEE 802.1D (self learning transparent Bridging)
- DHCP Server
- DNS Proxy
- Static Routing, RIPv1 and RIP

Application
- Netmeeting, ICQ, Real Player, QuickTime, DialPad, PC Anywhere,
- Telnet, SNTP, NNTP)

Radio Features

Wireless RF module Frequency Band
802.11g Radio: 2.4GHz
802.11b Radio: 2.4GHz
USA - FCC
2412 ~ 2462MHz (Ch1~Ch11)
Canada - IC
2412 ~ 2462MHz (Ch1~Ch11)
Europe - ETSI
2.4000 ~ 2.4835MHz (Ch1~Ch13)
Spain
2457 ~ 2462MHz (Ch10~Ch11)
France
2457~2472MHz (Ch10~Ch13)
Japan - STD-T66/STD-33
2412~2484MHz (Ch1~Ch14)

Modulation Type
- OFDM, CCK

Operating Channels IEEE 802.11b compliant:
- 13 channels (US, Canada)
- 3 channels (ETSI)
- 2 Channels (Spain)
- 4 Channels (France)
- 14 channels (Japan)

IEEE 802.11g compliant:
- 13 channels (US, Canada, Europe, Japan)

b-mode Modulation Rate-Output Power (dBm)
- 1Mbps 16 dBm
- 2Mbps 16 dBm
- 5.5Mbps 16 dBm
- 11Mbps 16 dBm

g-mode Modulation Rate-Output Power (dBm)
- 6Mbps 15 dBm
- 9Mbps 15 dBm
- 12Mbps 15 dBm
- 18Mbps 15 dBm
- 24Mbps 15 dBm
- 36Mbps 15 dBm
- 48Mbps 15 dBm
- 54Mbps 15 dBm

b-mode Modulation Rate- Receiver Typical Sensitivity (dBm)
- 1Mbps -90 dBm
- 2Mbps -88 dBm
- 5.5Mbps -85 dBm
- 11Mbps -84 dBm

g-mode Modulation Rate-Receiver Typical (Sensitivity dBm)
- 6Mbps -88 dBm
- 9Mbps -878 dBm
- 12Mbps -84 dBm
- 18Mbps -82 dBm
- 24Mbps -79 dBm
- 36Mbps -75 dBm
- 48Mbps -68 dBm
- 54Mbps -68 dBm

Environmental

SMC7404WBRB complies with the following standards:

Temperature: IEC 68-2-14
- 0 to 50 degrees C (Standard Operating)
- -40 to 70 degree C (Non-operation)
- Humidity
- 10%to 90% (Non condensing)
- Vibration: IEC 68-2-36, IEC 68-2-6
- Shock: IEC 68-2-29
- Drop: IEC 68-2-32

Dimensions
- 220 x 132 x 30 (mm)

Weight
- 550g

Power Input
- 12V/1A

IEEE Standards
- IEEE 802.3, 802.3u, 802.11g, 802.1D
- ITU G.dmt
- ITU G.Handshake
- ITU T.413 issue 2 - ADSL full rate

Standards Conformance Electromagnetic Compatibility
- CE, ETSI, R&TTE, ETS 300 328, ETS 300 826

Safety
- GS (EN60950), CB (IEC60950)

Internet Standards
- RFC 826 ARP
- RFC 791 IP
- RFC 792 ICMP
- RFC 768 UDP
- RFC 793 TCP
- RFC 783 TFTP
- RFC 1483 AAL5 Encapsulation
- RFC 1661 PPP
- RFC 1866 HTML
- RFC 2068 HTTP
- RFC 2364 PPP over ATM

SMC Networks Europe
Head Office
Edificio Conata II
Fructuós Gelabert 6-8 Planta 2
08970 - Sant Joan Despi
Barcelona
Spain
Telephone: +34 93 477 4920
Facsimile: +34 93 477 3774

SMC Networks Central Europe
Telephone: +49 (0) 89 92861-0
Facsimile: +49 (0) 89 92861-230

SMC Networks CIS
74, marshala Zhukova ave.
Moscow 123103 Russia
Telephone: +7 095 789 35 73
Facsimle: +7 095 789 35 73

SMC Nordic and Baltic
Telephone: +45 (0) 566 62283
Facsimile: +45 (0) 566 62286

SMC Networks Eastern Europe
Telephone: +420 607 96 6699
Facsimile: +420 235 36 3905

SMC Networks Italia
Telephone : +39 348 706 90 65

SMC Networks Netherlands
Telephone: +31 627 075227
Facsimile: +31 334 557 330

SMC Networks Ireland
Telephone: +353 61 34 0675
Facsimile: +353 61 34 0675

SMC Networks Sweden
Telephone:+46 (0)8 687 0700
Facsimile: +46 (0)8 87 62 62

SMC Networks North West Africa
Telephone: +216 71 23 66 16
Facsimile:+216 71 75 14 15

SMC Networks Sub-Saharan Africa
Telephone: +27 012 661 0232

SMC Networks South-East Europe
Telephone: +49 (0) 89 74 08 00 80
Facsimile: +49 (0) 89 74 08 00 81

SMC Networks Southern Europe
Telephone: +33 (0) 1 41 38 32 32
Facsimile: +33 (0) 1 41 38 01 58

SMC Networks Spain and Portugal
Telephone: +34 (0) 636 2043
Facsimile: +34 (0) 636 2044

SMC Networks United Kingdom
Telephone: +44 (0) 1932 86 6553

SMC is a registered trademark; and EtherPower, EZStart, SimulTasking, TigerSwitch and SuperDisk are trademarks of SMC Networks, Inc.
Other product and company names are trademarks or registered trademarks of their respective holders. © Copyright 2002 SMC Networks, Inc.